

A participative procedure to select indicators of policies for sustainable urban mobility. Outcomes of a national test

Gerardo Marletto · Francesca Mameli

Received: 29 March 2011 / Accepted: 11 January 2012 / Published online: 2 February 2012
© The Author(s) 2012. This article is published with open access at SpringerLink.com

Abstract

Background The assessment of policies for sustainable urban mobility features two basic characteristics: incommensurability and strong uncertainty. This is why multiple dimensions of evaluation and a structured room for collective deliberation and learning should be considered.

Methods A participative procedure is used to select a core set of performance indicators of policies for sustainable urban mobility. Citizen participation and stakeholder involvement are obtained through a national sample survey and a deliberative multi-criteria analysis, respectively. This procedure is applied to the Italian case.

Results Citizens are more oriented towards reducing private transport costs, air pollution and traffic accidents; stakeholders are more in favour of improving car-free accessibility and reducing the consumption of land and public space generated by urban mobility. The resulting core sets of indicators are highly sensitive to the threshold chosen for the selection. Using a lower cut-off threshold, four performance indicators are shared between the two sets: ‘CO₂ from transport’, ‘Quantity and quality of public transport’, ‘PM_x, COVNM, NO_x, CO from transport’, ‘Death and injuries from traffic accident’; using a higher cut-off threshold the two sets feature no intersection.

Concluding remarks Further testing at a local scale is needed in order to explicitly consider context-specific objectives, indicators and data; stronger interactions among experts, citizens and stakeholders are needed in order to avoid the generation of equivocal results.

Keywords Participation · Urban mobility · Sustainability indicators · National survey

G. Marletto (✉) · F. Mameli
DEIR and CRENoS, University of Sassari,
Via di Torre Tonda, 34,
07100 Sassari, Italy
e-mail: marletto@uniss.it

1 Introduction

Sustainable urban mobility is a well established environmental issue, not only in local plans, but also in international guidelines [1–4] and national legislations: this is the case of, among others, the French and Italian laws on Urban Mobility Plans, and the last generation of UK Local Transport Plans. Many large State programs are oriented towards sustainable urban mobility too: the Canadian ecoMOBILITY program and the Indian Sustainable Urban Transport Project are just two recent examples of an ever increasing list.¹

Policies for Sustainable Urban Mobility (PSUM) share two basic characteristics with all other environmental policies. The first one is their intrinsic incommensurability. Due to the co-existence of different objectives, criteria and values, the environmental, social and economic dimensions cannot in fact be compared using a common unit of measurement as suggested by standard techniques based on monetary evaluations (e.g. external costs and cost-benefit analysis). Other techniques that are able to use different metrics and explicitly take into account multiple dimensions of sustainability (e.g. indicator systems and multi-criteria analysis) are best suited for the purpose [5]. The second basic characteristic common to all environmental policies (and—among others—by PSUM) is the presence of strong uncertainty: the probabilities of future changes are not known ex-ante, nor is the set of possible changes. In these cases individuals and society feature bounded rationality [6]; hence policies can no longer be based on neutral values and given preferences, and they must make room for deliberation and learning. As argued by Vatn [7, p. 2211] “We move from *aggregating* individual measures or bids to

¹ Information on these two programs can be found respectively in <http://www.ecoaction.gc.ca/> and <http://urbanindia.nic.in/>.

reasoning over, and potentially *agreeing* on common priorities”. All these considerations led to the diffusion of participative procedures to establish environmental policies, which usually consist of a deliberation arena to involve citizens and stakeholders, combined with a structuring technique (usually a simplified multi-criteria) to achieve two equally important goals: easing mutual understanding and reaching final recommendations [8].

Similar considerations in favour of involving the people in a multi-dimensional approach to policy design, implementation and appraisal have been recently proposed by authoritative researchers with specific reference to sustainable transport [9–11]. More specific calls for the integration of stakeholders into multi-criteria procedures in the context of policies for sustainable transport were recently added to the debate; as clearly stated in the research report of the COST Action 356 “(...) the largest potential for MCDA [Multi-Criteria Decision Analysis] in decision making on sustainable development appears to lie in a combination of MCDA algorithms with participatory techniques and in their better integration into specific transport decision making contexts.” [12, p. 271]. The research we present here shares these theoretical and practical concerns and builds a participative procedure to select performance indicators for PSUM.² Such a procedure was implemented at a national scale, involving Italian experts, citizens and stakeholders.

The paper is structured as follows. In Section 2 the methodology of the participative procedure is analysed. Outcomes of the procedure are shown and discussed in Sections 3 and 4, respectively. The last section concludes.

2 The participative procedure: methodology

Table 1 shows the structure of the proposed procedure, which integrates top-down (expert-led) steps and bottom-up (participated) steps [14]. In Step 1, starting from a framework based on the dimensions of urban sustainability and the objectives of PSUM, we selected a first set of performance indicators. In Step 2 this framework was evaluated by citizens and by stakeholders: citizens’ opinion about dimensions and objectives were collected through a national survey (Step 2a); stakeholders were involved in a “stakeholder dialogue analysis”—i.e. a participated multi-criteria analysis—in which the dimensions were used as assessment criteria and the objectives as issues to be evaluated (Step 2b). In Step 3, the results of Step 2 were used to rank the initial set of PSUM performance indicators and to select the most relevant among them.

² Performance (or effectiveness) indicators are distinguished from monitoring (or status) indicators [13].

Table 1 A participative procedure to select performance indicators of policies for sustainable urban mobility (PSUM)

Step	Who	How	Results
1	Experts	Literature review Workshops and seminars	Conceptual framework of PSUM
2a	Citizens	National sample survey	Appraisal of dimensions and objectives of PSUM
2b	Stakeholders	Stakeholder dialogue analysis	
3	Experts	Analysis of results of Step 2	Sensitivity analysis Selection of performance indicators of PSUM

2.1 Step 1: a conceptual framework

In the first step of the procedure we further developed a framework which was already used by Isfort³ as a conceptual tool to select performance indicators of PSUM [15], and which was based on the dimensions of urban sustainability and the objectives of PSUM. The resulting conceptual framework follows the Thematic Indicator Development [16], which is explicitly conceived to manage sustainability policy issues, instead of the more diffused—but less policy oriented—Driving forces-Pressure-States-Impacts-Response approach [17].

Starting from a literature survey on indicators [18]⁴ and some workshops and seminars with experts, the three standard dimensions of social, environmental and economic sustainability were articulated into thirteen PSUM objectives, each of which was linked to one (single or composite) performance indicator (see Table 2). The social dimension of sustainability was split in two sub-dimensions: accessibility and liveability. Accessibility was then broken down into four objectives, considering that it depends on more than just transport factors, and that it can be operationalised in several ways [19]. The first objective refers to the ease with which urban services can be used without moving; the others explicitly take the different modes of urban transport into consideration. Then, we explicitly considered how urban liveability is affected by some negative effects of urban mobility: the erosion of public space caused by parked and circulating motorized vehicles, the generation of noise and air pollution, traffic accidents. The environmental dimension of sustainability was translated into three more standard objectives of PSUM: reducing greenhouse-gasses, waste and land consumption generated by mobility. Finally, the economic dimension of urban sustainability is pursued by reducing public and private transport costs. This top-down

³ For more information about Isfort, see below the section on acknowledgements.

⁴ For a synthesis of the review, see Appendix A.

Table 2 A conceptual framework of policies for sustainable urban mobility (PSUM)

Dimensions of urban sustainability		PSUM Objectives	PSUM Performance Indicators
Social sustainability	Accessibility	Increasing the alternatives to mobility	Public and private services accessible via telephone and computer
		Easing non-motorized mobility	Walkability and “cyclability”
		Easing private motorized mobility	Congestion
	Liveability	Easing public transport	Quantity and quality of public transport
		Reducing public space occupied by motorized vehicles	Vehicles- and vehicles*km per km ²
		Reducing noise generated by mobility	% of population exposed to harmful noise
		Reducing air pollutants generated by mobility	Main air pollutants from transport: PM _x , COVNM, NO _x , CO
Environmental sustainability	Increasing transport safety	Deaths and injuries from traffic accidents	
	Reducing greenhouse-gasses generated by mobility	CO ₂ from transport	
	Reducing waste generated by mobility	Waste from transport	
	Reducing land consumption generated by mobility	Land occupied by transport infrastructure	
Economic sustainability	Reducing mobility costs: public transport	Household expenditures for public transport	
	Reducing mobility costs: private transport	Household expenditures for private transport	

approach generated a core set of PSUM indicators that meets two of the main criteria of indicator selection: exhaustiveness (every objective of PSUM has its specific indicator) and efficiency (no redundant indicator is considered). Though every indicator of the set is derived from a single objective, some indicators have implications for multiple objectives and most of them have implications for multiple dimensions. It must be stressed that the detailed and operational specification of the indicators goes beyond the objectives of the present study; this is why some indicators are only broadly defined.

2.2 Step 2a: the national sample survey

Through the quarterly Isfort’s “Audimob” national survey on passenger mobility, a representative sample⁵ of the Italian population was asked to evaluate both the generic four dimensions of urban sustainability and the above list of 13 specific objectives. The sample was composed of 3,600 people, reproducing the main structural features of the Italian population aged 14–80 years: sex, age, professional status, region and size of the municipality of residence. The national survey employed the CATI (Computer Assisted Telephone Interviewing) technique, this is why respondents were not directly asked to rank the whole set of objectives and sustainability dimensions, nor were they asked to react to questions based on a Likert scale (both are difficult tasks for a phone interview), but they had to prioritize the importance of dimensions and objectives

⁵ Confidence interval: 1.65; confidence level: 95%.

according to the following qualitative scale: ‘Priority’; ‘Important but not priority’; ‘Useful but not urgent’. In order to avoid any averaging or aggregation of qualitative answers, only the percentage of respondents who rated a given dimension/objective as a “priority” was used to rank citizens’ opinion.

2.3 Step 2b: the “stakeholder dialogue analysis”

The “stakeholder dialogue analysis” is a participative multi-criteria technique that is successfully used to assist stakeholders in discussing a general political issue and in reaching a common position on it [20].

Because of budget constraints, we opted for a simplified “dialogue”⁶ that can be summarized as follows. First, we selected relevant Italian stakeholders among the following categories: national and local institutions; associations of consumers/users, environmentalists, workers and companies; political parties.⁷ Then, we asked (by e-mail or by fax) their representatives to individually weight the dimensions of urban sustainability mentioned above. Finally, we invited all stakeholders to attend a 1-day meeting during which a multi-criteria scheme was used to rank the objectives of PSUM. Two sub-groups were created to collectively score all PSUM objectives against one dimension of urban sustainability at a time; stakeholders used the following scores: 1 = useful, but non urgent; 2 = relevant, but not a priority; 4 = a priority. These evaluations generated four

⁶ A standard stakeholder dialogue analysis consists of four meetings aimed at setting and using a multi-criteria scheme.

⁷ For the detailed list of participating stakeholders, see Appendix B.

scores for each objective of PSUM, which were then aggregated by using the average weights assigned to dimensions by stakeholders. Two sensitivity tests were carried out to check the robustness of the results of the “dialogue”: in the first one, weighted average scores were calculated by using the weights assigned to dimensions by citizens (instead of those assigned by stakeholders); in the second test we lowered from 4 to 3 the score associated to those objective which was considered as “a priority” by stakeholders. In both cases we did not register any change in the final ranking of PSUM objectives.

2.4 Step 3: selection of performance indicators

Citizens’ and stakeholders’ evaluations on objectives of PSUM have been used to select the most relevant PSUM indicators among those ensuing from the first step of the procedure. The two selection criteria we used are very simple: 1) the higher the position of an objective in the ranking, the higher the relevance of the indicator associated with that objective; 2) a threshold value is arbitrarily set to cut off the less relevant indicators of PSUM. It must be stressed that using a cut-off threshold value is more correct than selecting the first X indicators: only in the first case the evaluations of citizens and stakeholders determine which and how many indicators are selected.⁸ Moreover, the threshold value can be lowered (raised) if more (less) resources are available to finance the data collection and processing activities needed to use the selected PSUM indicators. Obviously, there is no objective rule to set the threshold value, but the higher the difference between the value of the last of the selected indicators and the value of the first of the non-selected indicators, the lower the arbitrariness of the choice.

3 The participative procedure: results

3.1 Citizens’ opinion

According to citizens’ opinion, environmental sustainability and liveability are the most relevant issues (see Tables 3 and 4): reducing greenhouse-gasses, air pollutants, waste and accidents from transport are considered as priority by more than 58% of respondents. The objectives related to the dimension of accessibility rank low (see Table 4), except for the objective of easing public transport (that ranks 6th). Economic sustainability stands in a middle position, which is the average

⁸ For example, using the evaluations of citizens living in small and medium cities, relevant changes can be found not only in the ranking of objectives of PSUM, but also in the number of selected indicators. See below, paragraph 3.3.

Table 3 Citizens’ opinion towards the dimensions of urban sustainability

Dimensions of urban sustainability	Considered as a priority (%)	Ranking
Environmental sustainability	53.1	1°
Social sustainability: liveability	50.0	2°
Economic sustainability	48.4	3°
Social sustainability: accessibility	40.0	4°

of the 2nd and 8th positions reached by the objective of reducing private and public transport costs, respectively.

The results of the national survey were also analysed with reference to the size of cities where citizens live and to their preferred mode of transport.⁹ The ranking of two important objectives is correlated to urban size: easing public transport ranks 4th according to the opinion of citizens living in big cities, while it ranks 7th in medium cities and metropolitan belts, and 9th in small cities; reducing air pollutants ranks 1st in big cities, 2nd in metropolitan belts, 3rd in medium cities and 4th in small cities. Instead, the relevance of the issue of reducing private transport cost is inversely correlated to urban size: it ranks 1st in small cities and 5th in big cities.

A relevant difference between user groups concerns the issue of accessibility: easing non-motorised mobility ranks 2nd for cyclists (9th and 10th for public transport and car users, respectively); easing public transport ranks 2nd for public transport users (6th and 10th for car users and cyclists, respectively). Unexpectedly, easing private transport stays at the bottom of the ranking for all user groups.¹⁰

3.2 Stakeholders’ appraisal

Easing non motorized mobility and public transport are the two objectives of PSUM that achieved the maximum weighted score among stakeholders (see Table 5). Because of both low weights and very low scores, the two objectives of reducing private and public transport costs lie on the opposite side of the rankings. A low weighted score is also reached by the objective of easing private motorized mobility. Other objectives connected to the dimensions of environmental sustainability and liveability scored high in the ranking; while reducing noise and waste generated by transport are perceived as less relevant objectives of PSUM.¹¹

⁹ Data were also analysed with reference to other demographic and social variables (sex, age, region of residence, education, profession, etc.), but those results were not significantly different from those emerging from the whole sample.

¹⁰ For a more detailed analysis of segmented data, see [18].

¹¹ See Appendix C for detailed results.

Table 4 Ranking of the objectives of policies for sustainable urban mobility (PSUM) and selection of performance indicators according to citizens' opinion. Threshold: % = 48

PSUM objectives	Considered as a priority (%)	Ranking	Performance indicators of PSUM
Selected performance indicators of PSUM:			
Reducing greenhouse-gasses generated by mobility	71.0	1°	COx from transport
Reducing private transport costs	69.5	2°	Households expenditures for private transport
Reducing air pollutants generated by mobility	65.9	3°	Main air pollutants from transport: PMx COVNM, NOx, CO
Increasing transport safety	61.7	4°	Deaths and injuries from traffic accidents
Reducing waste generated by mobility	58.8	5°	Waste from transport
Easing public transport	49.9	6°	Quantity and quality of public transport
Reducing noise generated by mobility	49.5	7°	% of population exposed to harmful noise
Reducing public transport costs	48.1	8°	Households expenditures for public transport
Non selected performance indicators of PSUM:			
Reducing land consumption generated by mobility	45.0	9°	Land occupied by transport infrastructure
Easing non-motorized mobility	39.2	10°	Walkability and "cyclability"
Reducing public space occupied by motorized vehicles	36.8	11°	Vehicles- and vehicles*km per km ²
Easing private motorized mobility	33.7	12°	Congestion
Increasing the alternatives to mobility	30.6	13°	Public and private services accessible via telephone and computer

3.3 The selection of indicators

In order to select PSUM performance indicators, a threshold % of 48 was applied to citizens' opinion and a threshold score of 2.85 was applied to stakeholders' appraisal.

The eight indicators selected on the basis of citizens' opinion cover all dimensions of urban sustainability, of these three refer to the dimension of liveability (air pollutants, accidents and noise) and only one (public transport) refers to the dimension of accessibility (see again Table 4). Land consumption is the highest ranking indicator not selected by citizens. It must be noted that three more indicators would be cut off if we used a slightly higher threshold (50% instead of 48%).

Eight indicators came out of stakeholders' evaluation too (see again Table 5), but none of them refers to the economic dimension of urban sustainability. Three indicators of accessibility were selected, two of which (easing public and non-motorised transport) reached the maximum score. Noise ranks first among the indicators not selected by stakeholders. The number of selected indicators is halved if one uses a slightly higher threshold (3.0 instead of 2.8).

4 Discussion

4.1 Contribution to the relevant literature

The methodology we implemented to select PSUM indicators is based on two main tools: 1) a conceptual framework of dimensions and objectives of PSUM, which is used to select a first core set of performance indicators; 2) the participation of

citizens and stakeholders, in order to rank the selected indicators and—depending on the available resources—cut off the less relevant ones. The used methodology explicitly refers to the theoretical and practical work of two research groups, led by Mark Reed and Jacquelin Burgess, respectively [14, 20].

As far as we know, no reference can be found in the literature to the application of such an integrated methodology to the issue of sustainable urban mobility: many studies explicitly consider the dimensions of environmental, social and economic sustainability, some of them refer to objectives of policies for sustainable transport, but only two [21, 22] are based on the participation of stakeholders (and not of citizens) in order to select a limited number of indicators from a much longer initial list.¹²

We may then conclude that the main contribution of this study to the relevant literature is the integration of the participation of both citizens and stakeholders into the selection of PSUM indicators. The remaining part of this section discusses separately the three steps of the implemented procedure and its results.

4.2 Discussion of step 1 (a conceptual framework)

Though the definition of the initial conceptual framework is not the objective of our research (nor its added value), it must be emphasized that the starting reference to an already partially developed framework constitutes the main limitation of this study. We integrated the first version of the framework on the basis of a review of the relevant literature and meetings with

¹² See again Appendix A for more details.

Table 5 Ranking of objectives of policies for sustainable urban mobility (PSUM) and selection of performance indicators according to stakeholders' appraisal. Threshold: score = 2.85

Objectives of PSUM	Weighted average score ^a	Ranking	Performance indicators of PSUM
Selected performance indicators of PSUM:			
Easing non-motorized mobility	4.00	1°	Walkability and "cyclability"
Easing public transport	4.00	1°	Quantity and quality of public transport
Reducing land consumption generated by mobility	3.63	3°	Land occupied by transport infrastructure
Reducing public space occupied by motorized vehicles	3.05	4°	Vehicles- and vehicles*km per km ²
Increasing transport safety	2.89	5°	Deaths and injuries from traffic accidents
Reducing air pollutants generated by mobility	2.88	6°	Main air pollutants from transport: PMx, COVNM, Nox, CO
Reducing greenhouse-gasses generated by mobility	2.88	6°	CO2 from transport
Increasing the alternatives to mobility	2.87	8°	Public and private services accessible via telephone and computer
Non selected performance indicators of PSUM:			
Reducing noise generated by mobility	2.14	9°	% of population exposed to harmful noise
Reducing waste generated by mobility	2.12	10°	Waste from transport
Easing private motorized mobility	1.26	11°	Congestion
Reducing public transport costs	0.62	12°	Households expenditures for public transport
Reducing private transport costs	0.62	12°	Households expenditures for private transport

^a 1 = useful, but non urgent; 2 = relevant, but not a priority; 4 = a priority

other experts, but we remain aware that it needs further improvement. Inter alia: the objectives of urban density and social inclusion should be explicitly considered; all indicators—especially in the case of practical applications—should be better specified in order to check the availability of data and associate quantitative targets to objectives. At the same time, we remain convinced of our choice of referring to generic objectives and not to specific actions; otherwise the acceptability of a policy, instead of its relevance, is likely to be assessed.

4.3 Discussion of step 2 (ranking of PSUM objectives)

First of all, it must be said that we had to repeat the national survey after interviewers reported that respondents found some questions hard to understand. This is why we needed to clarify, for example, the difference between greenhouse gasses and local air pollutants, and between land consumption and the occupation of urban space; moreover, we had to add some practical examples to explain what we meant by 'waste generated by mobility'. It remains that some respondents could have responded superficially, without signalling to the interviewer that they did not completely understand the question.¹³ This is a problem which could be managed only by direct contact with citizens: ex-ante, through focus groups aimed at reaching a shared terminology; ex-post, through

structured arena, where citizens could deliberate on the results emerging from the survey.

There is one striking result emerging from the national survey: the objective of 'reducing private transport costs' ranks 2nd, which seems not so much consistent with the other high ranking objectives ('reducing greenhouse gases', 'reducing air pollutants', 'increasing safety', etc.). Actually, one should consider that most citizens are car drivers, who aspire at a more sustainable urban environment and—at the same time—are budget conscious; such an interpretation is confirmed by data segmentation: the need of reducing private costs ranks 5th in big cities (were the % of car drivers is lower) and 6th for public transport users. In more general terms, the analysis of the results of the national survey by urban size and transport mode shows that opinions on objectives of PSUM depend on the size of the city where citizens live and on their actual mobility behaviour.

Stakeholders' appraisal was more consistent: the objectives of easing private mobility and reducing its costs have been positioned at the bottom of the ranking; moreover, stakeholders did not explicitly refer to specific situations (even if one should suppose they generally refer to metropolitan contexts). Most important, though stakeholders were assigned the burdensome task of carrying out 52 assessments (13 objectives against four criteria), deliberation was easier than expected: the assignment of reaching shared evaluations pushed the mutual understanding between involved parties and the arrangement of all interests at stake. During the "dialogue", stakeholders acted as

¹³ This point was raised by an anonymous referee.

Table 6 Selection of indicators according to stakeholders' appraisal and citizens' opinion and with different thresholds

Selected performance indicators of PSUM	Lower threshold		Higher threshold	
	By stakeholders	By citizens	By stakeholders	By citizens
Walkability and “cyclability”	X		X	
Quantity and quality of public transport	X	X	X	
Land occupied by transport infrastructure	X		X	
Vehicles- and vehicles*km per km ²	X		X	
Deaths and injuries from traffic accidents	X	X		X
Main air pollutants from transport: PMx, COVNM, NOx, CO	X	X		X
CO ₂ from transport	X	X		X
Public and private services accessible via telephone and computer	X			
Households expenditures for private transport		X		X
Waste from transport		X		X
% of population exposed to harmful noise		X		
Households expenditures for public transport		X		

experts too; that is, they suggested some integrations to the proposed framework: in particular they asked for the explicit consideration of the issue of density¹⁴ and a greater articulation of the dimension of economic sustainability.

4.4 Discussion of step 3 (selection of PSUM indicators)

The two selections of PSUM indicators—based on citizens' opinion and stakeholders' appraisal, respectively—depend on the level of the thresholds which are used to cut off the less relevant indicators (see Table 6). When lower thresholds are used, only four performance indicators are shared between the two resulting sets: ‘CO₂ from transport’, ‘Quantity and quality of public transport’, ‘PM_x, COVNM, NO_x, CO from transport’, ‘Deaths and injuries from traffic accidents’ (and only one indicator is cut off from both lists: ‘congestion’). When higher thresholds are used, the two sets show no intersection.

There is no immediate explanation for the divergence between the two selections. We can only stress one relevant difference in the composition of the selecting groups: on one side, car users are almost 85% of the sample, which implies that their opinion strongly influences the results of the national survey; on the other side, only one stakeholder (out of 13) directly represented the interests related to the car. Moreover—as already stressed—all representative of the involved stakeholders live in a metropolitan context where the car is less used, and alternatives to the car are more diffused. Finally, it must be said that we had planned for stakeholders to know the evaluations of citizens before starting their “dialogue”, with the purpose of reducing the risk of generating equivocal results, but this was not possible because the results of the national

survey were not available when the stakeholder dialogue started (a delay caused by the already mentioned repetition of the national survey).

5 Conclusions and further research

In the research project presented here, the direct participation of citizens and stakeholders was used in order to manage the high level of uncertainty and incommensurability featured by environmental issues. A national survey and a “stakeholder dialogue analysis” (based on a multi-criteria technique) were integrated into an original procedure aimed at selecting a core set of performance indicators of policies for sustainable urban transport. The procedure proved valid in showing that citizens' opinion is context- and behaviour-specific, and generates a selection of indicators which diverges from that emerging from stakeholders' appraisal.

Most insights which result from this first national test stress the need of more widely shared basic concepts and less equivocal results, thus asking for a closer interaction between experts, citizens and stakeholders and for a more context-based approach to objectives, indicators and data. This is why a more articulated procedure is now proposed for future testing at a local scale (see Table 7). First of all, a new ‘step 2’ is added at the beginning of the procedure to check if the starting conceptual framework is exhaustive and widely shared, that is, if it covers all relevant issues connected to the sustainability of urban mobility, especially those which are context-specific. This new step would also be helpful for finding a widely understood terminology to be used in the national survey. Then, a new ‘step 3’ should help in making the basic framework more operational: a context-specific indicator should be associated to every objective; data should be

¹⁴ The objective of reducing land consumption ranks 3rd mainly because it was chosen by stakeholders as a proxy of the objective of increasing urban density.

Table 7 A participative procedure to select performance indicators of sustainable urban mobility policies (PSUM): the revised version (added steps in italics)

Step	Who	How	Results
1	Experts	Literature review Workshops and seminars	Conceptual framework (first version): dimensions, objectives and generic indicators
2a	<i>Citizens</i>	<i>Focus groups</i>	<i>Shared terminology</i>
2b	<i>Stakeholders</i>	<i>Stakeholder dialogue analysis (preliminary meeting)</i>	<i>Amendments to the first version of the conceptual framework</i>
3	<i>Experts</i>	<i>Analysis of results of Step 2</i>	<i>Conceptual framework (second version): dimensions, objectives, specific indicators and targets</i>
4a	Citizens	National sample survey	Appraisal of the dimensions and objectives of PSUM
4b	Stakeholders	Stakeholder dialogue analysis	
5	Experts	Analysis of results of Step 4	Sensitivity analysis
6	<i>(Experts) Citizens</i>	<i>Joint workshop or Citizens' jury</i>	<i>Deliberation on the results of Step 4</i> <i>Selection of indicators of PSUM</i>

provided about its current status and realistic target; the threshold used for the selection of indicators should be based on the cost of data collecting and processing. Finally, it must be ensured that the procedure is able to effectively manage the evaluations of citizens and stakeholders, even when they are divergent. Though this is an issue that needs deeper understanding, we think that assigning greater importance to citizens' opinion could be a solution. Stakeholders should know the evaluations of citizens before starting their meetings, and citizens may have "the last word" about the selection of indicators: a final "joint workshop" [23] or a "citizens' jury" [24] could close the participative procedure with the ambitious goal of generating serviceable results. Moreover, a direct

contact with experts could help citizens to avoid misunderstandings and superficial responses.

Acknowledgements The research presented here was promoted and funded by Isfort—Istituto Superiore di Formazione e Ricerca per i Trasporti, an Italian private research body specializing in the transport sector (<http://www.isfort.it/>). The research was partially co-funded by the University of Sassari (Italy). Authors thank Eleonora Pieralice of Isfort for data processing and three anonymous referees for their helpful comments.

Open Access This article is distributed under the terms of the Creative Commons Attribution License which permits any use, distribution and reproduction in any medium, provided the original author(s) and source are credited.

Appendix A

Table 8 Dimensions and indicators of sustainable urban mobility: a synthesis of the review of relevant studies

Ref.	Scale	Dimensions of sustainability	Indicators	Brief description
[21]	Urban	Accessibility, economic, environment, health, safety, governance	52	The study is aimed at selecting a limited number of indicators which may fulfil stakeholders' expectations of a sustainable urban transport system
[22]	Regional	Transport, social, environmental, economic	15	A stakeholder survey based on a multi-criteria technique is used to select the 15 best performing sustainable transport indicators out of an initial long list of 233
[25]	National	Transport, environmental	40 ^a	Indicator-based yearly reporting mechanism which monitors the integration and effectiveness of transport and environment strategies in the EU
[26]	Urban	Economic, social, environmental, transport activity.	47	Reviews the adequacy/deficiency of transport planning in Lahore (Pakistan) and recommends some measures for developing a more sustainable urban transport system
[27]	Urban	Economic, Social, Environmental, mobility	19	Develops a set of indicators for measuring the sustainability of Lyon's urban travel system (estimations are mainly based on households' travel survey data)
[28]	Urban	Economic, social, environmental	35	Integrated approach based on land-use transport models, spatial disaggregation of the data, economic/social evaluations, and multi-criteria analysis

Table 8 (continued)

Ref.	Scale	Dimensions of sustainability	Indicators	Brief description
[29]	Urban	Mobility	1	Evaluates the sustainability of the transportation system in San Antonio (Texas) using ‘vehicle travel miles’ as a key indicator
[30]	Urban	Transport, environment, infrastructures, technologies, spatial planning, transportation demand, Socio-economic	24	Employing multi-criteria analysis, this study identifies a set of indicators (and their relative importance) suitable for monitoring the urban mobility conditions of selected cities in Brazil and Portugal
[31]	National	Transport modes, social, environmental, economic	1 index	The sustainability index results from a two-steps aggregation of composite and individual indicators. All indicators are elasticities between non-transportation and transportation variables
[32]	Urban	Mobility	8 (1 index)	With the aim of monitoring mobility conditions in medium-sized cities, this study develops a so called “Sample Mobility Index” (composed of indicators related to walking, vehicle-use and cycling)
[33]	Urban	–	4	Suggests a methodology for quantifying land-use/urban-form based indicators based on remote-sensing technology, basic statistics, spatial analysis and modelled processes
[34]	Urban	Urban transport, urban design, urban management, urban environment	42	Harmonized set of indicators that could to be used for assessing the sustainability of an urban environment. Indicators are identified by taking into account a number of urban development-related concerns
[35]	–	Economic, social, environmental	34	List of recommended indicators disaggregated by relevance and dimensional category—based on a review of studies and best practices

^a Not all indicators are published every year

Appendix B

Table 9 Stakeholders participating to the “stakeholder dialogue analysis” on policies for sustainable urban mobility

Stakeholder	Representing
Institutions	
ANCI	Municipalities
Federmobilità	Local transport authorities
Ministry of the environment	National Government
Associations	
ANAV	Privately owned public transport companies
ANFIA	Producers of motor vehicles
ASSTRA	Publicly owned public transport companies
Comitati dei pendolari	Commuters
FIAB	Cyclists
FIT-CISL	Transport workers
Legambiente	Environmentalists
ORSA	Transport workers
UIL-Trasporti	Transport workers
Political parties	
Partito Democratico	Center-left voters

Appendix C

Table 10 Stakeholders' appraisal of the objectives of policies for sustainable urban mobility (PSUM): detailed results

PSUM objectives	Dimensions of PSUM (weights)				Weighted average score	Ranking
	Accessibility (0.248)	Liveability (0.287)	Environmental sustainability (0.278)	Economic sustainability (0.187)		
	Scores ^a					
Easing non-motorized mobility	4	4	4	4	4.00	1
Easing public transport	4	4	4	4	4.00	1
Reducing land consumption generated by mobility	4	4	4	2	3.63	3
Reducing public space occupied by motorized vehicles	4	2	4	2	3.05	4
Increasing transport safety	4	4	0	4	2.89	5
Reducing air pollutants generated by mobility	1	4	4	2	2.88	6
Reducing greenhouse-gasses generated by mobility	1	4	4	2	2.88	6
Increasing the alternatives to mobility	4	2	2	4	2.87	8
Reducing noise generated by mobility	1	4	2	1	2.14	9
Reducing waste generated by mobility	1	2	4	1	2.12	10
Easing private motorized mobility	2	2	0	1	1.26	11
Reducing public transport costs	1	0	0	2	0.62	12
Reducing private transport costs	1	0	0	2	0.62	12

^a 1 = useful, but non urgent; 2 = relevant, but not a priority; 4 = a priority

References

1. CEC—Commission of the European Communities (2006) Thematic strategy on the urban environment. COM (2005) 718 final, Brussels
2. CEC—Commission of the European Communities (2007) Towards a new culture for urban mobility. COM (2007) 551 final, Brussels
3. ECMT—European Conference of Ministers of Transport (2002) Implementing sustainable urban travel policies. OECD, Paris
4. ECMT—European Conference of Ministers of Transport (2002) Implementing sustainable urban travel policies: applying the 2001 key messages. OECD, Paris
5. Martinez-Alier J, Munda G, O'Neill J (1998) Weak comparability of values as a foundation for ecological economics. *Ecol Econ* 26:277–86
6. Simon HA (1982) Models of bounded rationality. MIT, Cambridge
7. Vatn A (2009) An institutional analysis of methods for environmental appraisal. *Ecol Econ* 68:2207–2215
8. Stagl S (2007) Emerging methods for sustainability valuation and appraisal. Final Report. SDRN—Sustainable Development Research Network, London
9. Booth C, Richardson T (2001) Placing the public in integrated transport planning. *Transp Policy* 8:141–149
10. Banister D (2008) The sustainable mobility paradigm. *Transp Policy* 15:73–80
11. May AD (2009) Improving decision-making for sustainable urban transport: an introduction to the DISTILLATE research programme. *Eur J Transp Infrastruct Res* 9:184–201
12. Joumard R, Gudmundsson H (eds) (2010) Indicators of environmental sustainability in transport. Les collections de l'INRETS, Lyon-Bron
13. Pearce B (2005) The use and abuse of indicators for evaluating land use and environmental planning—experience from the UK. In: Miller D, Patassini D (eds) Beyond benefit cost analysis. Ashgate, Aldershot, pp 127–150
14. Reed MS, Fraser EDG, Dougill AJ (2006) An adaptive learning process for developing and applying sustainability indicators with local communities. *Ecol Econ* 59:406–418
15. Federico A, Barbabella A (2006) Gli indicatori di valutazione delle politiche (Assessment indicators of policies). In: Marletto G (Ed) Gli strumenti per la programmazione (Tools for planning). Rapporti periodici, 5, Isfort, Roma
16. UNCSO—United Nations Commission on Sustainable Development (2001) Indicators of sustainable development: framework and methodologies. Background paper No. 3. United Nations, New York
17. EEA—European Environment Agency (1995) Europe's environment: the Dobris assessment. Copenhagen
18. Marni F, Marletto G (2009) Can national survey data be used to select a core set of indicators for monitoring the sustainability of urban mobility policies? Crenos Working Papers, 2009/11. CUEC, Cagliari
19. Geurs KT, van Wee B (2004) Accessibility evaluation of land-use and transport strategies: review and research directions. *J Transp Geogr* 12:127–140
20. Clark J, Burgess J, Dando N, Bhattachar D, Heppel K, Jones P, Murlis J, Wood P (1998) Prioritising the issues in local

- environment agency plans through consensus building with stakeholder groups. Technical Report w114. Environment Agency, Bristol
21. CIRT—Central Institute for Road Transport (2005) Sustainable urban transport for Pune metropolitan area. Final Report, Pune
 22. Castillo H, Pitfield DE (2010) ELASTIC—A methodological framework for identifying and selecting sustainable transport indicators. *Transp Res D* 15:179–188
 23. Davies G, Burgess J, Eames M, Mayer S, Staley K, Stirling A, Williamson S (2003) Deliberative mapping: appraising options for addressing “the kidney gap”. Final Report to the Wellcome Trust, London
 24. Kenyon W, Hanley N, Ceara N (2003) Citizens’ juries: an aid to environmental valuation? *Environ Plann C: Gov Policy* 19:557–566
 25. EEA—European Environmental Agency (2001–2010) TERM Reports 2000–2009, Copenhagen
 26. Imran M, Low N (2003) Time to change the old paradigm: promoting sustainable urban transport in Lahore, Pakistan. *World Transp Policy Pract* 9:32–39
 27. Nicolas JP, Pochet P, Poimboeuf H (2003) Towards sustainable mobility indicators: application to the Lyons conurbation. *Transp Policy* 10:197–208
 28. Lautso K, Spiekermann K, Wegener M, Sheppard I, Steadman P, Martino A, Domingo R, Gayda S (2004) PROPOLIS: planning and research of policies for land use and transport for increasing urban sustainability. Final Report, Helsinki
 29. Barker WG (2005) Can a sustainable transportation system be developed for San Antonio, Texas? *Transp Res Rec* 1924:120–128
 30. Costa MS, Silva ANR, Ramos RAR (2005) Sustainable urban mobility: a comparative study and the basis for a management system in Brazil and Portugal. In: Brebbia CA, Wadhwa LC (eds) *Urban transport and the environment in the 21st century*. WIT, Southampton, pp 323–332
 31. Rassafi AA, Vasiri M (2005) Sustainable transport indicators: definition and integration. *Int J Environ Sci Tech* 2:83–96
 32. Frei F (2006) Sampling mobility index: case study in Assis—Brazil. *Transp Res A-Pol* 40:792–799
 33. Zhang Y, Guindon B (2006) Using satellite remote sensing to survey transport-related urban sustainability—Part 1: methodologies for indicator quantification. *Int J Appl Earth Obs Geoinf* 8:149–164
 34. Häkkinen T (Ed) (2007) Trends and indicators for monitoring the EU thematic strategy on sustainable development of urban environment. Final report, Summary and recommendations. VTT Publications 643, Finland
 35. Litman T (2008) Well measured—developing indicators for comprehensive and sustainable transport planning. Victoria Transport Policy Institute, Victoria